Breathe Easy and Work Safe with Dynabrade!

VACUUM PENCIL GRINDERS

51622

· Each model includes urethane Vacuum Shroud, plus high-quality air line and flexible, durable vacuum hose,

 For connection to central vacuum system.

35.000 RPM

Model 51622 1/8" Collet Model 51624 3 mm Collet

 Includes 51739 Standard Vacuum Shroud.

50.000 RPM

Model 51629 1/8" Collet

Model 51631 3 mm Collet

 Includes 51739 Standard Vacuum Shroud.

60,000 RPM

Model 51632 1/8" Collet

Model 51634 3 mm Collet

 Includes 51739 Standard Vacuum Shroud.

Model 51623 1/8" Collet

- Extension model.
- Includes 51785 Extension Vacuum Shroud.

Model 51630 1/8" Collet

- Extension model.
- Includes 51785 Extension Vacuum Shroud.

Model 51633 1/8" Collet

- Extension model.
- Includes 51785 Extension Vacuum Shroud.

.4 HP VACUUM DIE GRINDERS

 Fach model includes urethane Vacuum Shroud for efficient capture of dust, debris and contaminants such as Hexavalent Chromium.

 For connection to central vacuum system.

• 1/4" collet.



Right Angle Models

Model 56715 12.000 RPM Model 56719 20.000 RPM

7° Offset Models

Model 56727 5,000 RPM

Model 56723 25,000 RPM

Gearless motor.



Straight-Line Models

Model 56751 5,000 RPM Model 56755 25.000 RPM

Gearless motor.

Breathe Easy and Work Safe with Dynabrade!

.7 HP VACUUM DIE GRINDERS

 Each model includes urethane Vacuum Shroud for efficient capture of dust, debris and contaminants such as Hexavalent Chromium.

For connection to central vacuum system.

• 1/4" collet, gearless motor.

Straight-Line Model

Model 56759 15,000 RPM

7° Offset Model

Model 56739 18,000 RPM



56759

56743

1 HP VACUUM DIE GRINDERS

• Each model includes urethane Vacuum Shroud.

· For connection to central vacuum system.

• 1/4" collet, gearless motor.

Straight-Line Models

Model 56743 *12,000 RPM* Model 56747 *20,000 RPM*



2" DIA., 7° OFFSET VACUUM DISC SANDERS

 Vacuum Shroud allows capture of dust, debris and contaminants.

 Includes 51344 Backing Pad, for 2" diameter locking-type abrasive discs.

.4 hp gearless motor, rear exhaust.

Self-Generated Vacuum

Model 51235 25,000 RPM

• 1" diameter vacuum port.

Central Vacuum

Model 51236 25,000 RPM

• 1-1/4" diameter vacuum port.



Breathe Easy and Work Safe with Dynabrade!

2" DIA., RIGHT ANGLE VACUUM DISC SANDERS

- · Vacuum Shroud allows capture of dust, debris and contaminants.
- Includes 51344 Backing Pad, for 2" diameter locking-type abrasive discs.
- .4 hp, rear exhaust.

Self-Generated Vacuum

• 1" diameter vacuum port.

Model 51225 *12,000 RPM*Model 51226 *15,000 RPM*Model 51227 *20,000 RPM*



• 1-1/4" diameter vacuum port.

Model 51230 *12,000 RPM*Model 51231 *15,000 RPM*Model 51232 *20,000 RPM*





3" DIA., RIGHT ANGLE VACUUM DISC SANDERS

- Vacuum Shroud allows capture of dust, debris and contaminants.
 Standard shroud may be trimmed for customized use.
- Includes 51346 Backing Pad, for 3" dia. locking-type abrasive discs.
- Unique "view port" allows operator to see edge of sanding disc.
- .4 hp, 15,000 RPM, rear exhaust.

Self-Generated Vacuum

1" diameter vacuum port.

Model 50210 Trimmed Shroud

Trimmed shroud (1" height).

Model 50570 Standard Shroud

Standard shroud (1-1/2" height).

Central Vacuum

• 1-1/4" diameter vacuum port.

Model 50211 Trimmed Shroud

• Trimmed shroud (1" height).

Model 50561 Standard Shroud

Standard shroud (1-1/2" height).



Breathe Easy and Work Safe with Dynabrade!

5" DIA., 1.3 HP, RIGHT ANGLE VACUUM DISC SANDER



- diameter vacuum port.
- Vacuum Shroud allows capture of dust and debris. Shroud brush assists in capture of airborne contaminants.
- · Ideal for use on non-ferrous surfaces such as fiberglass and composites. A vital tool in the marine industry and aftermarket!
- Includes 51150 Backing Pad plus mounting hardware, 95848 Gear Oil, 95541 Gear Oil Gun and vibration-dampening side handle.

7" DIA., 1.3 HP, RIGHT ANGLE **VACUUM DISC SANDER**



- 5/8"-11 spindle thread, 1-1/4" diameter vacuum port.
- Vacuum Shroud allows capture of dust and debris. Shroud brush assists in capture of airborne contaminants.
- · For use on non-ferrous surfaces such as carbon fiber, composites, fiberglass, turbine blades and more.
- Includes 51151 Backing Pad and flange, 95848 Gear Oil, 95541 Gear Oil Gun and vibration-dampening side handle.

Breathe Easy and Work Safe with Dynabrade!

VACUUM CUT-OFF WHEEL TOOLS

For use with optional diamond cut-off wheels.

3" Dia., Right Angle

Model 52538 .4 hp

- 12,000 RPM, rear exhaust.
- 1" diameter vacuum port.



3" Dia., Straight-Line


Model 52537 1 hp

- Extension model.
- 18.000 RPM. rear exhaust.
- 1" diameter vacuum port.

3" Dia., with Unique Cutaway Shroud & Flange

Model 52418 .7 hp

- 20,000 RPM, rear exhaust.
- Unique cutaway shroud design allows 1" wheel
- depth exposure. Non-marring plastic flange protects



Includes 94300 Composite Dynaswivel®.

• 1" diameter vacuum port.

4-1/2" Dia., 7° Offset

Model 52436 .7 hp

- 20,000 RPM, rear exhaust.
- 1" diameter vacuum port.

5" Dia., Right Angle

Model 52438 1 hp

- 12.000 RPM. rear exhaust.
- 1-1/4" diameter vacuum port.

Wheel Sold Separately





52537

52418

Breathe Easy and Work Safe with Dynabrade!

VACUUM ROUTERS

- .7 hp, 20,000 RPM, rear exhaust, 1" vacuum port.
- Accepts optional high-speed router bits with 1/4" dia. shank capacity.
- Non-marring composite base. Includes 94300 Composite Dynaswivel®.

3-1/2" Base Model

Model 51332

 Adjustable roller guide ensures consistent cut path on edge work.

4" Base Model

Model 51333

- Two handles for added support and ease of use.
- 4" dia. composite base offers enhanced stability.



.4 HP VACUUM DRILLS

- Includes collapsible vacuum shroud, which compresses around drill bit to effectively capture chips and debris.
- For connection to central vacuum system.

7° Offset Models

- Includes 1/4" drill chuck and key.
- 1-1/4" dia. vacuum port.

Model 52903 500 RPM

Model 52904 1,000 RPM

Model 52905 2,400 RPM

Model 52906 3,600 RPM

Model 52907 5,500 RPM

Angle Head Model

Model 53135 3,200 RPM

- Accepts 1/4"-28 threaded drill bits.
- 6' vacuum hose with 1" dia. port.





Breathe Easy and Work Safe with Dynabrade!

.7 HP VACUUM DRILLS PISTOL GRIP

- Includes collapsible vacuum shroud, which compresses around drill bit to effectively capture chips and debris.
- 1-1/4" dia. vacuum port for connection to central vacuum system.
- Each model includes drill chuck and key.

3/8" Drill Chuck

Model 53105 *950 RPM* Model 53103 *3,400 RPM* Model 53104 *4,500 RPM*

1/2 Drill Chuck

Model 53106 950 RPM



METAL FINISHING STATIONS

- Entraps Particles in Air/Water Mixing Zone
- Helps Reduce Potential Flammability of Workplace



12" x 21" Workable Surface

Model 64100

- 120 V (AC), tabletop design.
- Accepts up to 6" dual-wheel grinder/buffer.



18" x 36" Workable Surface

Model 64300

- 120 V (AC), tabletop design.
- Accepts up to 10" dual-wheel grinder/buffer.