



Features and benefits

High cutting power: very high stock removal.
Anti-clogging lubricant layer.
Suitable for many applications and materials and easy-release 'Tab'.
High performance and good surface finish.

Product specifications

D/C wt paper self-adhesive backing.
Lubricant coating (150 to 600).
Aluminum Oxide abrasive.
Modified synthetic resin bonding.

Application suggestions

Dry sanding.
Sanding and finishing of fillers, stoppers, primers, composite materials, wooden surfaces, wood coatings, walls and drywalls.
For self stick backing pads and hand blocks.

RHYNOSTICK

WhiteLine



Grit Range

16 20 24 30 36 40 50 60 80 100 120 150 180 220 240 280 320 360 400 500 600 800 1000 1200 1500 2000 2500 3000



Part # 50-XXX (Grit: 36 to 600)	5"	WhiteLine PSA Solid Discs
Part # 50-XXX (Grit: 80 to 600) LR	5"	WhiteLine PSA Solid Link Roll Discs
Part # 50-XXX (Grit: 80 to 600) LR25	5"	WhiteLine PSA Solid Link Roll Discs
Part # 51-XXX (Grit: 36 to 600)	5" 5 Hole	WhiteLine PSA Discs
Part # 56-XXX (Grit: 36 to 600)	5" 8 Hole	WhiteLine PSA Discs
Part # 60-XXX (Grit: 36 to 600)	6"	WhiteLine PSA Solid Discs
Part # 60-XXX (Grit: 80 to 600) LR	6"	WhiteLine PSA Solid Link Roll Discs
Part # 60-XXX (Grit: 80 to 600) LR25	6"	WhiteLine PSA Solid Link Roll Discs
Part # 64-XXX (Grit: 36 to 600)	6" 6 Hole	WhiteLine PSA Discs
Part # 66-XXX (Grit: 36 to 600)	6" 8 Hole	WhiteLine PSA Discs
Part # 80-XXX (Grit: 36 to 600)	8"	WhiteLine PSA Solid Discs
Part # 95-XXX (Grit: 36 to 400)	2 3/4" x 17 3/4"	WhiteLine PSA Strips
Part # 96-XXX (Grit: 36 to 400)	2 3/4" x 27 1/2 yds.	WhiteLine PSA Roll



RHYNOGRIP

WhiteLine




Discs



Strips



Rolls



Features and benefits

High cutting power: very high stock removal.
Anti-clogging lubricant layer.
Suitable for many applications/materials.
High performance and good surface finish.

Product specifications

D/C wt paper with velour backing.
Lubricant coating (150 to 600).
Aluminum Oxide abrasive.
Modified synthetic resin bonding.

Application suggestions

Dry sanding.
Sanding and finishing of fillers, stoppers, primers, composite materials, wooden surfaces, wood coatings, walls and drywalls.
For grip-system backing pads and hand blocks.

Grit Range

16 20 24 30 36 40 50 60 80 100 120 150 180 220 240 280 320 360 400 500 600 800 1000 1200 1500 2000 2500 3000

Part # 52-XXX (Grit: 36 to 600)	5"	WhiteLine Hook & Loop Solid Discs
Part # 54-XXX (Grit: 36 to 600)	5" 5 Hole	WhiteLine Hook & Loop Discs
Part # 55-XXX (Grit: 36 to 600)	5" 8 Hole	WhiteLine Hook & Loop Discs
Part # 59-XXX (Grit: 80 to 320)	5" 9 Hole	WhiteLine Hook & Loop Discs - Fits Festool Machine
Part # 61-XXX (Grit: 36 to 600)	6"	WhiteLine Hook & Loop Solid Discs
Part # 62-XXX (Grit: 36 to 600)	6" 6 Hole	WhiteLine Hook & Loop Discs
Part # 63-XXX (Grit: 36 to 600)	6" 8 Hole	WhiteLine Hook & Loop Discs
Part # 69-XXX (Grit: 40 to 600)	6" 9 Hole	WhiteLine Hook & Loop Discs - Fits Festool Machine
Part # 82-XXX (Grit: 36 to 600)	8"	WhiteLine Hook & Loop Solid Discs
Part # 83-XXX (Grit: 36 to 600)	8" 8 Hole	WhiteLine Hook & Loop Discs
Part # 92-XXX (Grit: 36 to 400)	2 3/4" x 17 1/2"	WhiteLine Hook & Loop Strips